

## SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** FLOOR ARMOR / INDUSTRIAL MAINTENANCE COATING (Color and Clear Coat)  
**Manufacturer Name:** POR-15, Inc.  
**Address:** P.O. Box 1235  
Morristown, NJ 07962-1235  
**General Phone Number:** 800-457-6715  
**Customer Service Phone Number:** 973-887-1999  
**Technical Product Information:** 800-457-6715  
**Emergency Phone Number:** 1-800-457-6715  
**CHEMTREC:** For emergencies in the US, call CHEMTREC: 800-424-9300  
**MSDS Format:** ANSI

## SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Xylene	1330-20-7	12 - 15 by weight	
Titanium dioxide	13463-67-7	2 - 3 by weight	
Parachlorobenzotrifluoride(PCBTF): Benzene, 1-chloro-4(Trifluoromethyl)	98-56-6	8 - 10 by weight	
n-Butyl Acetate	123-86-4	12 - 15 by weight	

## SECTION 3 - HAZARDS IDENTIFICATION

**Route of Exposure:** Inhalation, Skin.  
**Eye:** Can cause eye irritation.  
**Skin:** Can cause skin irritation.  
**Inhalation:** May be harmful if inhaled, may produce symptoms of central nervous system depression, including headache, dizziness, nausea, loss of balance.  
**Ingestion:** May be harmful if swallowed. May cause damage to the lining of the gastrointestinal tract.  
**Chronic Health Effects:**  
**Aggravation of Pre-Existing Conditions:**

## SECTION 4 - FIRST AID MEASURES

**Eye Contact:** In case of eye contact, immediately flush with plenty of water. Get medical attention.  
**Skin Contact:** Wash affected areas with water for 15 min. immediately remove contaminated clothing and shoes. Get medical attention.  
**Inhalation:** If inhaled, immediately move to fresh air. If breathing is difficult, give oxygen. Call a physician.  
**Ingestion:** Get medical attention. Immediately drink large quantities of water or milk.

## SECTION 5 - FIRE FIGHTING MEASURES

**Flammable Properties:**  
**Flash Point:** 76 deg F  
**Flash Point Method:** (Setaflash Closed Cup)  
**Auto Ignition Temperature:** Not determined  
**Fire Fighting Instructions:** Cool fire-exposed containers with water spray. Use water only as a blanket  
**Extinguishing Media:** Alcohol foam, carbon dioxide, dry chemical.  
**Unusual Fire Hazards:** Water may spread fire. (Products float on water) Heating may cause pressure to build-up and possible rupture of the container  
**Hazardous Combustion Byproducts:** Carbon Dioxide and Carbon Monoxide.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Environmental Precautions:** Environmental impact: Specific ecological testing has not been conducted on this product.  
**Spill Cleanup Measures:** Remove ignition sources. Add dry material to absorb spill. If large spill, dike to contain. Using recommended protective & explosion proof equipment pick up and containerize for recovery or disposal. Flush area with water, collect for disposal.  
**Other Precautions:**

## SECTION 7 - HANDLING and STORAGE

**Storage:** Keep away from heat, sparks and open flame. Ground containers during storage and transfer operations. Store way from heat & direct sunlight.

## SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

**Engineering Controls:** Local exhaust  
**Eye/Face Protection:** Chemical goggles  
**Skin Protection Description:** Neoprene gloves that are impervious to acrylates & dbo\_Section8.HandProtectionDescription  
**Respiratory Protection:** Respirator with organic vapor cartridge. Not applicable with local exhaust.

### EXPOSURE GUIDELINES

**Notes :**

## SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

**Physical State Appearance:** Liquid  
**Boiling Point:** No data  
**Melting Point:** No data  
**Density:** No data  
**Solubility:** No data  
**Evaporation Rate:** No data  
**Flash Point:** 76 deg F  
**Flash Point Method:** (Setaflash Closed Cup)  
**Auto Ignition Temperature:** Not determined  
**VOC Content:** For Light Grey: 285 gm/liter  
For Clear: 309 gm/liter  
For Dark Grey: 291 gm/liter  
For White: 330 gm/liter  
For Beige: 279 gm/liter  
For Tan: 330 gm/liter

## SECTION 10 - STABILITY and REACTIVITY

**Chemical Stability:** Stable under normal conditions.  
**Hazardous Polymerization:** Will not occur  
**Conditions to Avoid:** INSTABILITY CONDITIONS: High heat.  
**Incompatible Materials:** None

## SECTION 11 - TOXICOLOGICAL INFORMATION

## SECTION 12 - ECOLOGICAL INFORMATION

## SECTION 13 - DISPOSAL CONSIDERATIONS

## SECTION 14 - TRANSPORT INFORMATION

**DOT Shipping Name:** Flammable Liquids, N.O.S.  
**DOT UN Number:** UN1993  
**DOT Hazard Class:** 3  
**DOT Packing Group:** III

## SECTION 15 - REGULATORY INFORMATION

## SECTION 16 - ADDITIONAL INFORMATION

Copyright© 1996-2009 [Actio Software Corporation](http://www.actio.net). All Rights Reserved.  
<http://www.actio.net>