

## SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** **POR-15 Fuel Preservative/Stabilizer**  
**Product Use/Restriction:** Preservative  
**Manufacturer Name:** POR-15, Inc.  
**Address:** P.O. Box 1235  
Morristown, NJ 07962-1235  
**General Phone Number:** 800-457-6715  
**Customer Service Phone Number:** 973-887-1999  
**Technical Product Information:** 800-457-6715  
**Emergency Phone Number:** 1-800-457-6715  
**CHEMTREC:** For emergencies in the US, call CHEMTREC: 800-424-9300  
**MSDS Format:** ANSI

## SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
---------------	------	--------------------	---------

- by weight

## SECTION 3 - HAZARDS IDENTIFICATION

**Route of Exposure:**  
**Potential Health Effects:** Overexposure Effects: Eye irritation, skin irritation, skin irritation, headache, nausea, dizziness.  
**Eye:**  
**Skin:**  
**Inhalation:**  
**Ingestion:**  
**Chronic Health Effects:**  
**Signs/Symptoms:**  
**Target Organs:**  
**Aggravation of Pre-Existing Conditions:**

## SECTION 4 - FIRST AID MEASURES

**Eye Contact:** Immediately flush eyes with plenty of water for 15 to 20 minutes occasionally lifting eyelids. Get medical attention, if irritation or symptoms of overexposure persists.  
**Skin Contact:** Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists. Wash contaminated clothing thoroughly before re-use.  
**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention if necessary.  
**Ingestion:** If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.  
**Note to Physicians:**  
**Other First Aid:**

## SECTION 5 - FIRE FIGHTING MEASURES

**Flammable Properties:** Combustible liquid. At elevated temperatures, vapors can form an ignitable mixture with air. Vapors can flow along surfaces to distant ignition sources and flash back.  
**Flash Point:** 62.8°C (145°F)  
**Flash Point Method:** ASTM D56  
**Auto Ignition Temperature:**  
**Lower Flammable/Explosive Limit:**  
**Upper Flammable/Explosive Limit:**  
**Fire Fighting Instructions:**  
**Extinguishing Media:** Dry chemical (e.g. monoammonium phosphate, potassium sulfate, and potassium chloride), carbon dioxide, high expansion (proteinic) chemical foam, sand.  
**Unsuitable Media:**  
**Protective Equipment:** As in any fire wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.  
**Unusual Fire Hazards:** None; Combustible, keep from source of ignition.  
**Hazardous Combustion Byproducts:**

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Personnel Precautions:**

**Environmental Precautions:**

**Spill Cleanup Measures:** Contain liquid, keep from ignition source. Utilize absorbent material. Do not flush into sewer system.

**Other Precautions:**

## SECTION 7 - HANDLING and STORAGE

**Handling:** Avoid inhalation, skin contact.

**Storage:** No special precautions; try to keep cool & dry.

**Work Practices:**

**Special Handling Procedures:**

**Hygiene Practices:**

## SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

**Engineering Controls:** Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Localized mechanical exhaust is normally sufficient.

**Eye/Face Protection:** Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166. Contact lenses should not be worn.

**Skin Protection Description:** Cover as much of the exposed skin area as possible with appropriate clothing. If skin creams are used, keep the area covered to a minimum.  
& dbo\_Section8.HandProtectionDescription

**Respiratory Protection:** A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, spray painting, or any other circumstances where air purifying respirators may not provide adequate protection.

**Other Protective:** Eyewash and deluge shower should be available.

### EXPOSURE GUIDELINES

**Notes :**

## SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

**Flash Point:** 62.8°C (145°F)

**Flash Point Method:** ASTM D56

**Auto Ignition Temperature:**

## SECTION 10 - STABILITY and REACTIVITY

**Chemical Stability:** Stable

**Reactivity:**

**Hazardous Polymerization:**

**Conditions to Avoid:**

**Incompatible Materials:** Strong oxidizers, strong acids, oxygen

**Special Decomposition Products:**

## SECTION 11 - TOXICOLOGICAL INFORMATION

## SECTION 12 - ECOLOGICAL INFORMATION

## SECTION 13 - DISPOSAL CONSIDERATIONS

## SECTION 14 - TRANSPORT INFORMATION

**DOT Shipping Name:** Non-Regulated

**DOT UN Number:**

**DOT Hazard Class:** Non-Regulated

**DOT Packing Group:**

## SECTION 15 - REGULATORY INFORMATION

Copyright© 1996-2009 [Actio Software Corporation](http://www.actio.net). All Rights Reserved.  
<http://www.actio.net>