

## SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Accelerator/Hardener  
**Product Use/Restriction:**  
**Manufacturer Name:** POR-15, Inc.  
**Address:** P.O. Box 1235  
Morristown, NJ 07962-1235  
**General Phone Number:** 800-457-6715  
**Customer Service Phone Number:** 973-887-1999  
**Technical Product Information:** 800-457-6715  
**Emergency Phone Number:** 1-800-457-6715  
**CHEMTREC:** For emergencies in the US, call CHEMTREC: 800-424-9300  
**MSDS Format:** ANSI

## SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Aromatic Solvent	68333-23-3	- by weight	
1,6-Hexamethylene Diisocyanate based Polyisocyanate	28182-81-2	- by weight	
Ethyl 3-ethoxypropionate	763-69-9	- by weight	
Xylene	1330-20-7	1 - 1 by weight	

## SECTION 3 - HAZARDS IDENTIFICATION

**Route of Exposure:**

**Potential Health Effects:** Eyes: severe irritation; tearing skin, discoloration: drying; breathing: irritation, dizziness, unconsciousness (for solvent).

For isocyanates: coughing, irritation of mucous membranes and respiratory tract.

SKIN EFFECTS: Slight to moderate irritation; skin sensitizer in guinea pigs. No conclusive evidence has been developed to indicate that Glisten PC is carcinogenic, teratogenic or that it causes reproductive effects in animals or humans. Active resin in Glisten PC has been reported by NIOSH to be mutagenic to Salmonella Typhimurium bacteria in the presence of a mammalian liver activation system. There is not full agreement in the scientific community on the significance of these Ames test results and their relationship to human safety in assessing the risk of cancer in man.

**Eye:** HUMAN EFFECTS OF OVEREXPOSURE:  
Liquid, vapors, or aerosols are irritating to the eyes and can cause lachrymation (tearing effect). Corneal damage can occur; however, indications are that the damage is reversible and does not result in permanent injury.

**Skin:** HUMAN EFFECTS OF OVEREXPOSURE:  
Glisten PC reacts with skin protein and tissue moisture and can cause localized irritation as well as discoloration. Prolonged contact could produce reddening, swelling, or blistering and, in some individuals, skin sensitization resulting in dermatitis.

**Inhalation:** HUMAN EFFECTS OF OVEREXPOSURE:  
Inhalation of Glisten PC vapors in concentrations above 0.02 ppm can produce irritation of the mucous membranes in the respiratory tract, running nose, sore throat, productive cough and a reduction of lung function. Extensive exposures to concentrations well above the TLV could lead to bronchitis, bronchial spasm and pulmonary edema. These effects are usually reversible. However, due to low volatility, high exposures are not anticipated except if the material is overheated or sprayed as an aerosol into the air. Hypersensitivity pneumonitis has also been reported. Another type of response is hyperreactivity or hypersensitization. Persons with a preexisting unspecific bronchial hyperreactivity or persons with a specific isocyanate hypersensitivity (as a result of previous repeated overexposure or a single large dosage) will respond to small isocyanate concentrations at levels well below the TLV of 0.02 ppm. Symptoms could be immediate or delayed and include chest tightness, respiratory distress or asthmatic attack.

**Ingestion:** HUMAN EFFECTS OF OVEREXPOSURE:  
Ingestion could result in irritation and some corrosive action in the mouth, stomach tissue and digestive tract. However, it is not considered a common occupational route of exposure.

**Chronic Health Effects:**

**Signs/Symptoms:**

**Target Organs:**

**Aggravation of Pre-Existing Conditions:**

## SECTION 4 - FIRST AID MEASURES

<b>Eye Contact:</b>	Immediately flush eyes with plenty of water for 15 to 20 minutes occasionally lifting eyelids. Get medical attention, if irritation or symptoms of overexposure persists.
<b>Skin Contact:</b>	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists. Wash contaminated clothing thoroughly before re-use.
<b>Inhalation:</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention if necessary. Asthmatic-type symptoms may develop and may be immediate or delayed up to several hours. Treatment is essentially symptomatic.
<b>Ingestion:</b>	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Give 250 ml of milk or water to drink. Consult physician.
<b>Note to Physicians:</b>	
<b>Other First Aid:</b>	

## SECTION 5 - FIRE FIGHTING MEASURES

<b>Flammable Properties:</b>	Combustible liquid. At elevated temperatures, vapors can form an ignitable mixture with air. Vapors can flow along surfaces to distant ignition sources and flash back.
<b>Flash Point:</b>	51.1°C (124°F)
<b>Flash Point Method:</b>	TCC
<b>Auto Ignition Temperature:</b>	246°C (475°F)
<b>Lower Flammable/Explosive Limit:</b>	1%
<b>Upper Flammable/Explosive Limit:</b>	7%
<b>Fire Fighting Instructions:</b>	Avoid spreading burning liquid with water for cooling purposes.
<b>Extinguishing Media:</b>	Dry chemical (e.g. monoammonium phosphate, potassium sulfate, and potassium chloride), carbon dioxide, high expansion (proteinic) chemical foam, sand.
<b>Unsuitable Media:</b>	
<b>Protective Equipment:</b>	As in any fire wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
<b>Unusual Fire Hazards:</b>	Keep work areas free of hot metal surfaces and other sources of ignition.
<b>Hazardous Combustion Byproducts:</b>	

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

<b>Personnel Precautions:</b>	
<b>Environmental Precautions:</b>	
<b>Spill Cleanup Measures:</b>	Eliminate source of ignition of vapors, wear protective clothing while cleaning up; absorb on sand, clay, or absorbent material.
<b>Other Precautions:</b>	

## SECTION 7 - HANDLING and STORAGE

<b>Handling:</b>	
<b>Storage:</b>	STORAGE TEMPERATURE (min/max): 32 deg F (0 deg C)/122 deg F (50 deg C)  AVERAGE SHELF LIFE: 12 months @ 77 deg F (25 deg C)  Store in tightly closed container. At maximum storage temperatures noted, material may slowly polymerize without hazard. Ideal storage temperature range is 50-81 deg F (10-27 deg C).
<b>Work Practices:</b>	
<b>Special Handling Procedures:</b>	
<b>Hygiene Practices:</b>	

## SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

<b>Engineering Controls:</b>	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Ventilation as required to maintain air concentrations below TLV's. If material is spray-applied, ventilation should be provided and air supplied respirators worn. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.
<b>Eye/Face Protection:</b>	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166. Contact lenses should not be worn.
<b>Skin Protection Description:</b>	Cover as much of the exposed skin area as possible with appropriate clothing. If skin creams are used, keep the area covered to a minimum. & dbo_Section8.HandProtectionDescription
<b>Respiratory Protection:</b>	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister approved for use in isocyanate containing environments may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. In spray applications you must protect against exposure to both vapor and spray mist. An air-supplied respirator is strongly recommended for spray application. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate

Other Protective:

protection.  
Eyewash and deluge shower should be available.

#### EXPOSURE GUIDELINES

Notes :

#### SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Flash Point: 51.1°C (124°F)  
Flash Point Method: TCC  
Auto Ignition Temperature: 246°C (475°F)

#### SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.  
Reactivity:  
Hazardous Polymerization: Will not occur under normal conditions.  
Conditions to Avoid: Temperatures below 0°C (32°F) or above 50°C (122°F). To maintain freshness:  
Avoid contact with water, alcohols, amines, strong bases, metal compounds or surface active materials.  
Incompatible Materials:  
Special Decomposition Products:

#### SECTION 11 - TOXICOLOGICAL INFORMATION

#### SECTION 12 - ECOLOGICAL INFORMATION

#### SECTION 13 - DISPOSAL CONSIDERATIONS

#### SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name: Paint or Paint related material  
DOT UN Number: UN1263  
DOT Hazard Class: 3  
DOT Packing Group: III

#### SECTION 15 - REGULATORY INFORMATION

#### SECTION 16 - ADDITIONAL INFORMATION

Copyright© 1996-2009 [Actio Software Corporation](http://www.actio.net). All Rights Reserved.  
<http://www.actio.net>